

LONG THREADED TERMINAL

[download pdf \(50 Kb.\)](#)

High Polished Stainless Steel - AISI 316



Cat. No.	Wire Size (mm.)	G (UNF)	L1 (mm.)	L2 (mm.)	L3 (mm.)	D (mm.)	Kw	Break Load (Kg.)	Kg./100	PACK (Pcs.)
05M0306A	3	1/4"	132	86	38	6,4	5	1.300	2,6	BULK
05M0406A	4	1/4"	137	81	45	7,5	6	1.300	3	BULK
05M0408A	4	5/16"	147	93	45	7,5	6	2.350	4,3	BULK
05M0508A	5	5/16"	156	93	51	9	7	2.350	5,2	BULK
05M0510A	5	3/8"	176	115	51	9	7	3.500	7,7	BULK
05M0611A	6	7/16"	206	123	64	12,6	11	4.700	14,5	BULK
05M0711A	7	7/16"	211	123	70	14,2	12	4.700	16,8	BULK
05M0612A	6	1/2"	224	149	64	12,6	11	5.400	18,7	BULK
05M6312A	1/4"	1/2"	224	149	64	12,7	11	5.400	18,7	BULK
05M0712A	7	1/2"	232	149	70	14,2	12	5.400	21,3	BULK
05M0812A	8	1/2"	247	149	84	16	14	5.400	25,2	BULK
05M0816A	8	5/8"	282	184	84	16	14	8.000	37,4	BULK
05M1016A	10	5/8"	292	179	89	17,8	15	8.000	41,6	BULK

Note: All breakloads are determined by thread.

The user is responsible for choosing the proper cable diameter and for correct assembly.

[back](#)