


THREAD TERMINALS DRILLED FOR SPLIT PIN

[download pdf \(50 Kb.\)](#)

Stainless Steel - AISI 316



For right hand thread drilled use 93 instead of 90.
 For left hand thread drilled use 94 instead of 91.
 For all other measures, please refer to Cat. No. 90 & 91.

Cat. No. RIGHT	Cat. No. LEFT	G (UNF)	Wire Dim. (mm.)	Wire Dim. (inch.)	L1 (mm.)	L2 (mm.)	L3 (mm.)	D (mm.)	Break Load (Kg.)	Kg./100	PACK (Pcs.)
900306A	910306A	1/4"	3	1/8"	100	38	48	6,35	1.300	2,2	BULK
900406A	910406A	1/4"	4	5/32"	110	45	48	7,5	1.300	2,5	BULK
900408A	910408A	5/16"	4	5/32"	117	45	57	7,5	2.350	3,8	BULK
900508A	910508A	5/16"	5	3/16"	123	51	57	9	2.350	4	BULK
900510A	910510A	3/8"	5	3/16"	130	51	63	9	3.500	5,3	BULK
900610A	910610A	3/8"	6	-	145	64	63	12,58	3.500	8,4	BULK
906310A	916310A	3/8"	-	1/4"	145	64	63	12,58	3.500	8,3	BULK
900611A	910611A	7/16"	6	-	157	64	68	12,58	4.700	10	BULK
900711A	910711A	7/16"	7	9/32"	162	70	68	14,2	4.700	12,7	BULK
900612A	910612A	1/2"	6	-	162	64	80	12,58	5.400	10,8	BULK
906312A	916312A	1/2"	-	1/4"	162	64	80	12,58	5.400	11	BULK
900712A	910712A	1/2"	7	9/32"	170	70	80	14,2	5.400	14	BULK
900812A	910812A	1/2"	8	5/16"	185	83	80	16	5.400	19,2	BULK
900816A	910816A	5/8"	8	5/16"	203	83	100	16	8.000	25,9	BULK
909516A	919516A	5/8"	-	3/8"	210	89	100	17,8	8.000	31,1	BULK
901016A	911016A	5/8"	10	-	212	89	100	17,8	8.000	30,1	BULK
909520A	919520A	3/4"	-	3/8"	230	89	120	17,8	13.000	38,7	BULK
901020A	911020A	3/4"	10	-	230	89	120	17,8	13.000	39,1	BULK
901220AX	911220AX	3/4"	12	-	265	120	120	21,4	13.000	48,6	BULK
901320A	911320A	3/4"	-	1/2"	266	120	120	21,4	13.000	48,6	BULK
901422A	911422A	7/8"	14	-	308	140	140	25	17.000	78,7	BULK
901625A	911625A	1"	16	5/8"	363	160	170	28	24.000	126	BULK
901927A	911927A	1-1/8"	19	3/4"	425	200	180	34,5	25.500	210	BULK
902230A	912230A	1-1/4"	22	7/8"	480	230	200	40,5	31.000	313	BULK

902636A	912636A	1- 3/8"	26	1"	550	280	220	46	43.000	470	BULK
---------	---------	------------	----	----	-----	-----	-----	----	--------	-----	------

Note: All breakloads are determined by thread.

The user is responsible for choosing the proper cable diameter and for correct assembly.

[back](#)

The logo for allRIG, featuring the word "allRIG" in a stylized, lowercase, italicized font. The "a" and "l" are connected, and the "R" is larger and more prominent.

Buscarons, 6 - 08022 Barcelona | Tel.: (+34) 934 186 632 | Fax: (+34) 934 185 648

E-Mail: info@allrig.net | www.allrig.net